

PRODUCT PASSPORT №

**Viscous petroleum road bitumen grade BND 50/70
GOST 33133-2014**

Name of the NTD for sampling: GOST 2517-2012
OKPD 2 code: 19.20.42.121
Date of manufacture of the product: 8/19/2021
Date of sampling: 8/20/2021
Test date: 8/20/2021
Sampling location: R 5.6
Batch number: 5.6
Batch size (weight) t: 80

Certificate of conformity No.
ROSS RU. HB61. H24788.
Valid until 07.06.2024.



№	Parameter	Method	Specified value GOST	Result
Main indicators				
1	Penetration, 0,1 mm, at 25 °C not lower than	GOST 33136	51-70	67
2	Ring-and-ball softening point, °C not lower than	GOST 33142	51	53,6
3	Ductility, cm, at 0 °C, not lower than	GOST 33138	3,5	3,6
4	Breaking point, °C, not higher than	GOST 33143	-16	-21
5	Flash points in open cup*, °C, not lower than	GOST 33141	230	280
6	Change of mass after aging, %, max	GOST 33140	0,6	0,5
7	Change of softening point after aging, °C, max	GOST 33140 GOST 33142	7	6
Additional indicators				
8	Ductility, cm, at 25 °C, not lower than	GOST 33138	60	62
* The indicator is periodic, determined at least once a month.				

Conclusion: Viscous petroleum road bitumen grade BND 50/70 corresponds GOST 33133-2014 to the above indicators

Scope of application of the product in accordance with paragraph 5 of Article 1 of the technical regulations of the Customs Union "Road safety" (TR CU 014/2011).